

# CRT48 with power steering

## Ride-on Trowels



**WACKER  
NEUSON**  
*all it takes!*



### **Innovative control concept for more productivity: CRT48-PS**

Thanks to its optimal maneuverability and high surface capacity as well as a balanced power-to-weight ratio, the CRT48-PS achieves high productivity with excellent results. The electro hydraulic joystick control enables accurate maneuvering and virtually fatigue-free operation. Controlled by joystick modulations, the valves of the hydraulic control cylinder are triggered by electrical signals. The CRT 48-PS offers a choice of two control modes to accommodate operator preference in varying site conditions.

- Electro hydraulic control concept offers true power steering
- Very precise control operation
- Virtually fatigue-free operation
- Choice of two control modes
- Ideal for large pours and elevated deck applications where lighter weight machines are preferred

## CRT48 with power steering Technical specifications

	CRT48-37V-PS	CRT48-57K-PS	CRT48-35L-PS* (N/A USA)
<b>Dimensions</b>			
L x W x H Shipping in	107 X 55.75 X 64	107 X 55.75 X 65	107 x 55.75 x 64
L x W x H Operating in	101 X 51 X 58	101 X 51 X 59	101 x 51 x 58
<b>Weights</b>			
Shipping weight lb	1,664	1,796	1,760
Operating weight lb	1,300	1,456	1,420
<b>Blades and finishing data</b>			
Troweling diameter in	48	48	48
Quantity of blades	10	10	10
Blades (Combination) in	18 X 8	18 x 8	18 x 8
Blades (Finsh) in	18 X 6	18 x 6	18 x 6
Blades (Float) in	18 X 10	18 x 10	18 x 10
Pitch range °	0-25	0 - 25	0 - 25
Rotor speed (min. / max.) rpm	25/170	25/150	25/150
<b>Engine / Motor</b>			
Engine / Motor	Air-cooled, V-Twin, gasoline	Liquid-cooled, four-cylinder, gasoline	Liquid-cooled four-cylinder diesel
Engine / Motor manufacturer	Briggs & Stratton	Kubota	Kohler
Displacement in <sup>3</sup>	61	93.8	84
Operating performance (SAE J1349) hp	37		
Operating performance (SAE J1995) hp		57	
Operating performance (ISO 1585) hp			34.9
RPM / speed (operating) rpm	4,000	3,600	3,600
Fuel type	Unleaded Gasoline	Unleaded Gasoline	Diesel
Fuel consumption US gal/h	2.8	2.5	1.6
Tank capacity Fuel US gal	6.5	6.5	6.5
Tank capacity Oil US qt	2.4	6.3	5.4
Runtime h	2.5	2.6	4

\*Not available in the United States

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations. Copyright © 2019 Wacker Neuson SE.