XW SPLIT DECK TILT

Tilt Trailer

Model	Deck Length	Overall Width	Between the Fenders	Deck Height	Axle Capacity	Radial Tire Size	Main Frame	Crossmembers	Tongue
P6CAM154STTXW (4’ Stat, 15’ Tilt)	19’	102”	83”	22”	6,000 lbs.	235/80R 16LRE	6”x4”x5/16” Angle	3” Channel	6” Channel @ 8.2 lbs.
P7CAM154STTXW (4’ Stat, 15’ Tilt)	19’	102”	83”	22”	7,000 lbs.	235/80R 16LRE	6”x4”x3/8” Angle	3” Channel	6” Channel @ 10.5 lbs.
P8CAM154STTXW (4’ Stat, 15’ Tilt)	19’	102”	83”	23”	8,000 lbs.	215/75R 17.5LRH	6”x4”x1/2” Angle	3” Channel	6” Channel @ 10.5 lbs.

FEATURES

EZ Lube Axles
Oil Bath Axle (8 Ton)
Torflex Axles
Electric Brakes (2) Axles
Pallet Fork Carrier (N/A w/Gooseneck)
Adjustable Hydraulic Cushion Cylinder
Removable Diamond Plate Fenders
7K Bolt-On Drop Leg Jack (12K on 7 Ton & 8 Ton)
LED Lights – Rubber Mounted
Adjustable 2-5/16” Ball Coupler or Pintle
(8) D-Ring – 5/8”
Aluminum Tool Box
Pressure Treated Decking (Oak on 8 Ton)
Silver Wheels
(2) Banjo Eye Tie-Downs
Solar Charged Breakaway
Sealed Wiring Harness
Spare Tire Mount
7-Way SAE Plug
Safety Chains
Epoxy Primer
Polyurethane Paint Finish
Colors (standard): Black, Yellow
Three Year Warranty

OPTIONS

Extra Deck Length (21’ Max.)
Power Up & Power Down
Spare Tire & Wheel
12K Bolt-On Drop Leg Jack (Standard on 7 Ton & 8 Ton)
Oak Deck (Standard on 8 Ton)
Mud Flaps
Custom Colors
Contact your local dealer for more options

© 2019 Novae Corp. All Rights Reserved.