

# COMPACTION ROLLERS

## 6000

- High Performance
- Excellent Visibility
- Best in Class Operator Comfort
- Long Working Life
- Optimized for Serviceability
- Available with Steel or Combination Drums



**MAULDIN**

## COMPACTION ROLLERS

OPERATION		6000	DRUMS		6000
Engine		24 hp Kubota	Front		
Brakes-Service		Hydrostatic		Thickness	0.5"
Brakes-Parking		Yes		Width	47"
Drive System				Diameter	26"
Travel Speed		0-10 mph			
Fuel Capacity		12 gal	Rear:	Thickness	0.4"
Hydraulic Oil Capacity		10.5 gal		Width:	47"
Water Capacity		54 gal		Diameter	26"
Steering		Gear pump with constant displacement			
<b>DIMENSIONS</b>			<b>WATER SYSTEM</b>		
Length		98.5"	Tank		54 Gal
Width		52.75"	Type		Pressurized
Height (w/o ROPS/Cab)		68.75"	Scrapers		Spring Loaded Rubber
Wheelbase		67"			
Curb Clearance		21.8"	<b>COMPACTIVE EFFECT</b>		
			Amplitude		0.020"
Turning Radius		8.5' / 12.5' (inside/outside)	Vibration (VPM)		3,960/3,660 vpm
			Centrifugal Force		7,600/6,500 lbs
<b>WEIGHT</b>			<b>OPTIONAL EQUIPMENT</b>		
Operating Weight		5,700 Lbs	Combination Steel/Rubber		
Max Operating Weight		6,000 Lbs			
			Feb-18		

Calder Brothers Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacture at any time without notice or obligation.

**Sold & Serviced by:**



**Calder Brothers Corporation**  
**250 E. Warehouse Ct.**  
**Taylors, SC 29687**  
**Phone (864) 244-4800**  
**Fax (864) 244-5007**  
**www.CalderBrothers.com**