

## MT-300 and MT-600 HOT TACK SPRAYERS

- **Hydraulically Driven Asphalt Pump with Forward and Reverse Material Flow**
- **Reverse Suction Reclaims Material from System**
- **Two Position Optional Spray Bar with Cab Control  
Allows Outer Nozzel View from Tow Vehicle Mirror**
- **Tank Recirculate Valve**
- **Single, 8" Diameter Flue with Triple Tank Pass**
- **Optional Features:**
  - Diesel Burner with Thermostat Control**
  - Tank Insulation**



**\*\*Optional Equipment Shown\*\***

# TACK TANKS

<b>WEIGHTS</b>	<b>Model MT-300</b>	<b>Model MT-600</b>	<b>TANK CONSTRUCTION</b>	<b>Model MT-300</b>	<b>Model MT-600</b>
Operating, Tank Empty	2,250 lbs / 1,020 kg	2,850 lbs / 1,290 kg	Tank Heads	Dished & Flanged, Welded Inside & Out	
Torsion Spring Axle(s)	Single	Dual	Tank Shell	Standard Oval Cross Section	
Axle Capacity	6,000 lbs / 2,721 kg	6,000 lbs / 2,721 kg	Baffle	NA	with Crawl Hole
Capacity	300 Gal / 1,135 L	600 Gal / 2,270 L	Manhole	20" / 51cm	
<b>DIMENSIONS</b>			Contents Gauge	Yes	
Overall Length	169" / 430 cm		<b>ENGINE</b>		
Overall Width	96.5" / 245 cm		Fuel Type	Gasoline	
Loading Height	62" / 158 cm	70" / 178 cm	Power	9.5 HP (SAE/1394)	
Tires	225/75R15		Power	7 Kw	
Brakes	Electric, Single Axle		Type and Cooling	1 Cylinder - Electric Start, Air Cooled	
<b>PERFORMANCE DATA</b>			<b>FLUID CAPACITIES</b>		
Asphalt Pump	8 GPM / 30 LPM, Reversible Hydraulic Driven		Solvent Tank	9 Gal. / 19 L	
Heating, Type	Propane, Twin Burners		Hydraulic Tank	9 Gal. / 19 L	
Heating Flue	Diameter: 8" / 20 cm		Diesel Tank, (if equipped)	9 Gal. / 19 L	
	Single Flue Tube with Triple Tank Pass		<b>TRAILER, SAFETY</b>		
Hand Spray Wand	Single Nozzle		Hitch, Pintle Eye	2 3/4" / 70 mm	
Hand Spray Hose	40 feet / 12 meters		Braking	Electronic Break-Away System with Safety Chains	
Hand Spray Hose Reel	Manual Wind		Wiring	Trailer Lighting, Standard	
<b>OPTIONAL SPRAY BAR DATA</b>			<b>OPTIONAL EQUIPMENT</b>		
Asphalt Pump	35 GPM / 130 LPM, Reversible Hydraulic Driven		Skid Mounting, Ball Hitch in lieu of Pintle Eye, Fire Extinguisher, Diesel Fired Burner with Thermostatic Control, Tank Insulation, 110 volt Overnight Heat,		
Width	8 feet / 2.44 meters		Non-Recirculating Spray Bar, Joint Spray Nozzle, Pencil Thermometer		
Controls	In-Cab Control		Special Paint		
Thermometer Type	Dial Thermometer, 50° - 550° Fahrenheit				

Feb-15

Calder Brothers Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacture at any time without notice or obligation.

**Sold & Serviced by:**



**Calder Brothers Corporation**  
**250 E. Warehouse Ct.**  
**Tailors, SC 29687**  
**Phone (864) 244-4800**  
**Fax (864) 244-5007**  
**www.CalderBrothers.com**