

TERRAMAC® RT14 RUBBER TRACK CARRIER

Standard RT14 Specs

The Terramac® RT14 features a 28,000 lb. carrying capacity and is sure to get noticed for its ability to tackle the heavy loads. Customizable attachments available, contact your local Dealer or Terramac® factory for more details.

DIMENSIONS	
Full Length	20' 6"
Full Height	10' 5"
Width Over Tracks	9' 8"
Min Ground Clearance	24"
Front Overhang	3' 1.5"
Track Gauge (Center-to-Center)	7'
Track Width	31.5"
Undercarriage Length (Idler to Drive Hub)	12' 4"
Dump Bed Loading Height Over Side	6' 7"
Height of Rock Bed Side (Vessel)	20"
Length of Rock Bed (Vessel)	11' 6"
Width of Rock Bed (Vessel)	9'
Dumping Angle	60°
Machine Weight (no bed)	28,726 lbs.
Machine Weight (with rock bed)	34,260 lbs.

ENGINE	
Manufacturer	Cummins
Model	QSB 6.7 T4F
Displacement	408 cu. in.
Horsepower	310 HP @ 2200 RPM
Electrical System	12 VDC
Battery	(2) GRP 31, 1125 CCA each
Fuel Capacity	82 gallons



HYDRAULICS	
Transmission	HST
Drive Pump Max Flow (x2)	64 gpm / side
Drive Pump Max Pressure	5,500 PSI
Tandem Gear Pump Max Flow	
Front Section (Aux Output)	30 gpm @ 3000 PSI
Rear Section (HST Drive)	25 gpm @ 500 PSI

PERFORMANCE	
Max. Carrying Capacity	28,000 lbs.
Travel Speed - 1st Gear	4.0 mph
Travel Speed - 2nd Gear	6.8 mph
Gradability	58% (30°)
Turning Radius	Zero Turn
Ground Pressure (loaded)	7.4 PSI
Ground Pressure (unloaded)	4.9 PSI

TERRAMAC[®] RT14 RUBBER TRACK CARRIER

Standard RT14 Units & Dimensions

